


T, TS, TSG FOR MANHOLES, POLES, TUNNELS

T

- + Line joint closure for joining of cable lengths
 - + One optional branching
 - + One side entry/exit - simplifies lift-up from manhole to service vehicle/tent
 - + Lockable with item 11 218 056 Locking Cap
 - + Included: Blind plug SS, 2x24 mm Cable Bushings for 9-24 mm cables, kit for hot sealing (shrink tube, emery cloth), Absorbent Bag and
 - + Instruction Manual 719 990 01
 - + Branch-off for all types of cable bushings
- Multicassettes are ordered separately



T	Interior diameter/ lid height, mm	Exterior diameter/ total height, mm	Max no of Multi-cassettes	No of optional branchings	Max splicing capacity			
					Single fibre: 24/36 per Multi-cassette	4-ribbon: 72 per Multi-cassette	8-ribbon: 144 per Multi-cassette	12-ribbon: 108 per Multi-cassette
Art. No. 11 100 201	240/50	270/140	4	1	96/144	288	576	432
11 100 203	240/70	270/160	6	1	144/216	432	864	648
11 100 205	240/150	270/250	10	1	240/360	720	1440	1080
11 100 207	240/200	270/330	16	1	384/576	1152	2304	1728

TS


- + Oval entry for cable with uncut fibres. (midspan)
- + Two open cable bushing ports
- + One side entry/exit - simplifies lift-up from man-hole to service vehicle/tent
- + Lockable with item 11 218 056 Locking Cap
- + Included: Kit for oval entry heat shrink sealing (shrink tube, emery cloth and branch-off clip), Absorbent Bag and Instruction Manual 719 990 01
- + Branch-off for all types of cable bushings
- + Cable Bushings, Multicassettes and Blind Plugs ordered separately



TS	Interior diameter/ lid height, mm	Exterior diameter/ total height, mm	Max no of Multi-cassettes	No of optional branchings	Max splicing capacity			
					Single fibre: 24/36 per Multi-cassette	4-ribbon: 72 per Multi-cassette	8-ribbon: 144 per Multi-cassette	12-ribbon: 108 per Multi-cassette
Art. No. 11 100 401	240/50	270/150	4	2	96/144	288	576	432
11 100 403	240/70	270/170	6	2	144/216	432	864	648
11 100 405	240/150	270/260	10	2	240/360	720	1440	1080
11 100 407	240/200	270/340	16	2	384/576	1152	2304	1728

TSG

- + Oval entry for cable with uncut fibres. (midspan)
- + 6 pre-mounted and pre-sealed branch-off cable entries, - 4 with 16 mm and 2 with 25 mm
- + 12 Microcable connections also possible with cold sealing onto the four 16 mm cable entries, with TKT S 3x7
- + One side entry/exit - simplifies lift-up from man-hole to service vehicle/tent
- + Lockable with item 11 218 056 Locking Cap
- + Included: Kit for oval entry heat shrink sealing (shrink tube, emery cloth and branch-off clip), Absorbent Bag and Instruction Manual 719 990 01
- + Multicassettes ordered separately



TSG	Interior diameter/ lid height, mm	Exterior diameter/ total height, mm	Max no of Multi-cassettes	No of optional branchings	Max splicing capacity			
					Single fibre: 24/36 per Multi-cassette	4-ribbon: 72 per Multi-cassette	8-ribbon: 144 per Multi-cassette	12-ribbon: 108 per Multi-cassette
Art. No. 11 100 501	240/50	270/160	4	6	96/144	288	576	432
11 100 503	240/70	270/180	6	6	144/216	432	864	648
11 100 505	240/150	270/270	10	6	240/360	720	1440	1080
11 100 507	240/200	270/350	16	6	384/576	1152	2304	1728