




T-BLF - BLOWN FIBRE CLOSURES


T-BLF 2X40



- + Line joints and branchings for max 40 mm ducts with blown fibre
- + Open cable bushing ports, suitable for ducts or cables
- + Suitable for above ground and man-hole installations
- + No IP tightness value stated - Tightness relying on sealing of total duct installation
- + Lockable with item 11 218 056 Locking Cap
- + Included: Instruction Manual 719 990 01
- + Blind Plugs, Cable Bushings, Shrink Tubes, and Multicassettes are ordered separately

T-BLF 2x40 Inline	Interior diameter/ lid height, mm	Exterior diameter/ total height, mm	Max no of Multi-cassettes	No of optional branchings	Max splicing capacity			
					Single fibre: 24/36 per Multi-cassette	4-ribbon: 72 per Multi-cassette	8-ribbon: 144 per Multi-cassette	12-ribbon: 108 per Multi-cassette
Art. No.								
11 100 811	240/50	270/140	4	3	96/144	288	576	432
11 100 813	240/70	270/160	6	3	144/216	432	864	648
11 100 815	240/150	270/250	10	3	240/360	720	1440	1080
11 100 817	240/200	270/330	16	3	384/576	1152	2304	1728


T-BLF 4x40



- + Line joints and branchings for max 40 mm ducts with blown fibre
- + Open cable bushing ports, suitable for ducts or cables
- + Suitable for above ground and man-hole installations
- + No IP tightness value stated - Tightness relying on sealing of total duct installation
- + Lockable with item 11 218 056 Locking Cap
- + Included: Instruction Manual 719 990 01
- + Blind Plugs, Cable Bushings, Shrink Tubes, and Multicassettes are ordered separately

T-BLF 4x40 Inline	Interior diameter/ lid height, mm	Exterior diameter/ total height, mm	Max no of Multi-cassettes	No of optional branchings	Max splicing capacity			
					Single fibre: 24/36 per Multi-cassette	4-ribbon: 72 per Multi-cassette	8-ribbon: 144 per Multi-cassette	12-ribbon: 108 per Multi-cassette
Art. No.								
11 100 821	240/50	270/140	4	1	96/144	288	576	432
11 100 823	240/70	270/160	6	1	144/216	432	864	648
11 100 825	240/150	270/250	10	1	240/360	720	1440	1080
11 100 827	240/200	270/330	16	1	384/576	1152	2304	1728

T-BLF 2x40 PARALLEL ENTRY



- + Line joints and branchings for max 40 mm ducts with blown fibre
- + Open cable bushing ports, suitable for ducts or cables
- + Suitable for above ground and man-hole installations
- + No IP tightness value stated - Tightness relying on sealing of total duct installation
- + Lockable with item 11 218 056 Locking Cap
- + Included: Instruction manual 719 990 01
- + Blind Plugs, Cable Bushings, Shrink Tubes, and Multicassettes are ordered separately

T-BLF 2x40 Parallel Entry	Interior diameter/ lid height, mm	Exterior diameter/ total height, mm	Max no of Multi-cassettes	No of optional branchings	Max splicing capacity			
					Single fibre: 24/36 per Multi-cassette	4-ribbon: 72 per Multi-cassette	8-ribbon: 144 per Multi-cassette	12-ribbon: 108 per Multi-cassette
Art. No.								
11 100 801	240/50	270/140	4	1	96/144	288	576	432
11 100 803	240/70	270/160	6	1	144/216	432	864	648
11 100 805	240/150	270/250	10	1	240/360	720	1440	1080
11 100 807	240/200	270/330	16	1	384/576	1152	2304	1728