

LVABC Fitting Connectors

■ EPC Series - Temporary Earth Point Connector

Application

Temporary connection from LVABC - temporary bonding, earthing, generation point.

Features

- Provides a fully sealed, waterproof connection
- No need to strip cable to make the connection
- Torque controlling shear heads on all bolts
- Tightening bolts do not come into contact with live components
- Stainless steel fasteners.



Product Number	Type	Mains Cable Range	Bonding Bolt Size	Pack Size
EPC1-401	Earthing / temporary connector point with screw on cap	50 to 150mm ²	M12	10
EPC1-401-TC	Earthing/temporary connector point with rubber cap with lanyard no hardware	50 to 150mm ²	M12	10
EPC1-401-B150	Earthing / temporary connector point with hardware 150mm bolt suit Sicame earthing clamp	50 to 150mm ²	M12	10

Products on this page are unsuitable for multi-stranded flexible cables.


■ Water Blocking Connector

Application

In-line connector with solid barrier to prevent migration of moisture from old water laden cables into new connections fittings. Also suitable for transitionjointing of dissimilar sized cables.

Features

- Provides a fully sealed, waterproof connection
- Torque controlling shear heads on all bolts
- In-line transition joint
- Factory fitted cable tail
- Comes complete with a test point.



Product Number	Cable Range mm ²
WBC125	1.5-25mm
WBC125E	1.5-25mm

Testing Specification

AS/NZS 4396

Insulation piercing for 0.6/1kV aerial bundles cables.