

Fuses and Fuse Switches

■ PFV Series - 100 Amp Service Fuse Disconnect

Application

For pole mounted fusing of overhead house service up to 100A.

Constructed with no corrosive materials to provide long in-service life in outdoor environments.

Lower fuse carrier accepts BS 58x22 round fuse elements and is fitted with high-visibility house number plates to avoid incorrect disconnection.

Features

- UV stabilised, impact resistant and flame retardent body
- Insulation piercing connectors on both line and load side
- Tested to AS/NZS 60269.2.1
- Top mounted stainless steel bracket M8 fixing bolt insulated from active components
- Underside cable entry to IPC connectors creating a natural drip loop
- Conductor seal fully encapsulates conductor end
- Utilises shear head technology
- Shear-head bolts located at end of fuse for easier installation
- UV stabilised bird guard over cable seals

- Completely waterproof bi-metallic connection
- Perforated body to provide cross-flow ventilation
- Range of brackets to suit various applications
- IP44
- Fuse is full vented to allow air circulation around fuse
- Standard pig tail stick to operate service fuse base
- Optional high-visibility house numbering system
- Fuse is fully vented.

Products on this page are unsuitable for multi-stranded flexible cables.



PFV100695

Product Number	Description	Cable Range	Pack Size
PFV100695	Fuse - Switch disconnect, 100A	6-95sqmm	20
PFV100695E	Fuse - Switch disconnect, 100A with high-visibility clips	6-95sqmm	20
PFV100695E IDPO	Fuse - Switch disconnect, 100A with high-visibility clips and orange house number identification plate	6-95sqmm	20
PFV100695E IDPW	Fuse - Switch disconnect, 100A with high-visibility clips and white house number identification plate	6-95sqmm	20
PFV100695E IDPB	Fuse - Switch disconnect, 100A with high-visibility clips and blue house number identification plate	6-95sqmm	20
PFV100KIT	Fuse - 100A, pole mount with PFVAB1 swan neck adaptor	6-95sqmm	12
PFV100695 WB	Fuse - Switch disconnect, 100A, 6-95sqmm to 1.5-25 water blocking connector pre-installed	6-95 1.5-25	20
PFV100695 WB KIT	Fuse - Switch disconnect, 100A, 6-95sqmm to 1.5-25 water blocking connector pre-installed with TTD101NBKX/12 neutral connection in kit	6-95 1.5-25	20



Note: Add suffix 'E' for addition of yellow shear-head indicator