

Mechanical Connectors

■ MF Series - Mechanical Ferrules for MV

Description and Application

Mechanical shear-head connectors for general cable jointing applications up to 33kV. The bolts are designed to shear flush with the body of the connector.



Features

- Tinned aluminium alloy body
- Shear-head bolts
- Central bore in barrel
- Centre moisture/oil barrier
- Chamfered barrel ends
- Range taking
- Compact design
- Designed for use with battery powered impact drivers
- Copper or aluminium conductors



Product Number	Conductor* Range (mm) ²	Length x OD (mm)	Bolts
MF20/1-2	25 - 95	80 x 25	4 x 13 mm A/F
MF20/2-2	70 - 150	90 x 30	4 x 17 mm A/F
MF20/3	120 - 240	100 x 36	4 x 17 mm A/F
MF20/3D1	50 - 240	100 x 36	4 x 17 mm A/F
MF20/3.5	185 - 300	140 x 38	4 x 22 mm A/F
MF20/3.5D	95 - 300	140 x 38	4 x 22 mm A/F
MF20/4	240 - 400	170 x 42	6 x 22 mm A/F
MF20/5	400 - 630	200 x 50	6 x 22 mm A/F

**Suitable for class 1 & 2 copper and aluminium conductors (AS1125) only. Not suitable for flexible cables. Also suitable for class 1 or 2 sector shaped conductors. Please ask for details.*

© Sicame Australia Pty Ltd. The information presented here is subject to change without notice.