

LV Heat Shrink

■ Medium Walled Tube - LVHTM-U & LVHTM-C Series

Description and Application

- Power utility approved
- Made from thermally stabilised cross-linked polyolefin blended with synthetic rubber
- UV resistant and weather-proof
- Coated tubes are lined with a polyamide based hot-melt adhesive
- A range of other sizes are available on request
- Alternative coatings available on request

Features

- Cross-linked polyolefin
- High shrink ratio
- Polyamide based hot-melt adhesive lined
- UV resistant and weather-proof
- Other sizes, types and lengths available

Coated Medium Wall

Product Code	Diameter (mm) (Exp/Rec)	Standard Cut Length (mmm=)
LVHTM20/6-C-1000	20/6	1000
LVHTM30/10-C-1000	30/10	1000
LVHTM40/12-C-1000	40/12	1000
LVHTM40/12-C-1200	40/12	1200
LVHTM50/16-C-1000	50/12	1000
LVHTM50/16-C-1500	50/16	1500
LVHTM60/20-C-1000	60/20	1000
LVHTM95/25-C-1000	95/25	1000
LVHTM115/34-C-1000	115/34	1000
LVHTM140/42-C-1200	140/42	1200
LVHTM160/50-C-1500	160/50	1500
LVHTM180/58-C-1500	180/58	1500
LVHTM200/65-C-1500	200/65	1500
LVHTM235/65-C-1500	235/65	1500

Uncoated Medium Wall

Product Code	Diameter (mm) (Exp/Rec)	Standard Roll Length (mm)
LVHTM20/6-U	20/6	30
LVHTM30/10-U	30/10	30
LVHTM50/16-U	50/16	25
LVHTM60/20-U	60/20	25
LVHTM85/25-U	85/25	20



LV Heat Shrink

■ Heavy-Walled Tube

Description and Application

- Power utility approved
- Made from thermally stabilised cross-linked polyolefin blended with synthetic rubber
- UV resistant and weather-proof
- Coated tubes are lined with a polyamide based hot-melt adhesive
- A range of other sizes are available on request
- Alternative coatings available on request

Features

- Cross-linked polyolefin
- High shrink ratio
- Polyamide based hot-melt adhesive lined
- UV resistant and weather-proof
- Other sizes, types and lengths available



Heavy Wall

Product Code	Diameter (mm) (Exp/Rec)	Standard Cut Length (mm)
LVHTH30/10-C-1000	30/10	1000 - coated
LVHTH30/10-C-1500	30/10	1500 - coated
LVHTH40/12-C-1000	40/12	1000 - coated
LVHTH40/10-C-1500	40/12	1500 - coated
LVHTH50/16-U-1500	50/16	1500 - uncoated
LVHTH/16-U	50/16	30 metre roll-uncoated